



- 00204-350 PRO-STRUT® RECTANGULAR GLASS BACKBOARD WITH ALUMINUM-FACED STEEL FRAME
- 00326-XXX PADDING KIT FOR RECTANGULAR GLASS BACKBOARD - BOLT-ON (EACH) SEE PAGE No. B-326 FOR AVAILABLE COLORS
- 00227-000 PADDING KIT FOR RECTANGULAR GLASS BACKBOARD - TAPE-ON (PAIR)

See B-326

See B-227

REVISION	DATE	porter® No.
JRG	1-28-91	
RJM	12-12-91	CUSTOMER No.
CHANGE MNT'G HARDWARE	6-1-97	
DATE		
3-1-1989		

00204-350
3'-6" x 6'-0" RECTANGULAR GLASS BACKBOARD WITH ALUMINUM-FACED STEEL FRAME (FAN-MOUNT CENTERS)

THIS PRINT IS THE PROPERTY OF PORTER ATHLETIC EQUIPMENT COMPANY AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

porter®
 WORLD LEADER
 IN QUALITY SPORTS EQUIPMENT
 2500 S. 25th AVENUE
 BROADVIEW, ILLINOIS 60155
 www.porter-ath.com

DRAWING BY	RJM
CHECKED BY	EAS
PAGE No.	B-204-35

SPECIFICATIONS

PORTER No. 00204-350 PRO-STRUT® **OFFICIAL 3'-6" x 6' RECTANGULAR GLASS BACKBOARD** **WITH UNITIZED STEEL FRAME**

(Replacement Backboard with Fan Shaped Backboard Mounting Centers)

Backboard shall be 3'-6" x 6'-0" to meet all NCAA, NFHS and professional requirements.

Backboard frame shall be of a welded, unitized construction fabricated from heavy wall rectangular steel tubing, aluminum-faced for professional appearance. Unitized frame shall include two vertical struts located at 35" centers incorporating key hole slot type mounting plates located on mounting centers to replace any standard fan shaped backboard without the use of additional hardware or support structure. Struts shall be reinforced by a horizontal rectangular steel tube with a unique spacer sleeve arrangement at the upper two goal mount hole locations to transmit undue loading during slam-dunks, etc. directly through the glass and into the rear frame.

Unitized frame shall be designed to allow the bottom two goal mount holes to pass beneath the glass section to further alleviate stress on the glass. Rear backboard frame shall be finished in a durable neutral gray powder-coated finish.

Glass shall be provided in 1/2" thick, fully tempered (heat-treated) glass section with uniform load and impact strength. Official white border and target area is "fired in" permanently on front side of glass section so that it cannot wear away. Glass section shall be secured to unitized rear frame by means of an attractive, L-shaped brushed aluminum extrusion for optimum durability. Front perimeter frame shall be secured to unitized rear frame with structural truss head rivets. Glass section shall be fitted with shock absorbing neoprene material to cushion and protect the glass section. Goal mounting holes (4) to be on standard 5" (horizontal) x 4-1/2" (vertical) mounting centers (for use with Porter Model No. 00221-000, 00223-000 or 00225-000 goals).

Backboard protected by limited lifetime warranty.

Backboard not recommended for outdoor use.

OPTIONAL ITEMS TO SPECIFY

- See Page No. B-326 for specifications on Porter No. 00326-XXX Backboard Padding Kits.
- See Page No. B-227 for specifications on Porter No. 00227-000 Backboard Padding Kit.